



A | temperature cabinet adjustable from 9 to 15° to mature your wines in the best possible conditions.



EAN Code : 3543290002752

| | |
|-------------|----------------------|
| Range : | OXYGEN |
| Model : | OXM1T182NPD |
| Fonction : | Ageing |
| Capacity* : | 182 Bottles** |



A constant temperature due to the dual Heating/Cooling controls.



Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

| CONFIGURATION | Storage shelves | Sliding shelves | Capacity** |
|--------------------------------------|-----------------|-----------------|------------|
| Maximum Configuration (100% sliding) | - | 10 | 141 |
| Mixed Configuration | 2 | 1 | 177 |
| Minimum Configuration (100% storage) | 3 | 0 | 182 |
| Standard Configuration | 3 | 0 | 182 |

UNIVERSAL SHELF

Universal shelf : AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level : 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



« Storage »
72 Bottles



« Sliding »
12 Bottles



« Presentation »
6 + 36 Bottles

ArteVino AOHUI shelf has a label holder :



| Description | Reference | EAN Code |
|--|-----------|---------------|
| Single Solid beechwood universal shelf | AOHUI | 3543290002783 |

GENERAL FEATURES

| | |
|--|---------------------------|
| Gross weight, packaged(kg)* | : 85,8 |
| Net weight (kg)* | : 70,8 |
| Dimensions in packaging H x W x D (mm) | : 1595 x 700 x 750 |
| Dimensions H x W x D(mm) | : 1480 x 680 x 700 |
| Color scheme | : Black |

| | |
|--|-------------------|
| Energy efficiency rating | : A+ |
| Acoustic emissions (dB(A))***** | : 37 |
| Electrical power (W)** | : 65 |
| Electrical intensity (A)** | : 0.30 |
| Consumption per 24h (KWh) **** | : 0.33 |
| Annual energy consumption AEC* (kWh/year) **** | : 121 |
| Ambient temperature operating limit | : 0 - 35°C |

- ✓ Digital electronic controls
- ✓ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit > Automatic « Winter function »
- ✓ Temperature fault alarm icon
- ✓ Interior lining of dimpled aluminium
- ✓ Solid door
- ✓ Hygrometry ensured by the principle of thermodynamic pump
- ✓ 2 adjustable feet
- ✓ Lock
- ✓ Storage grid in the low part
- ✓ Inox Handle

* Standard configuration
 ** Traditional Bordeaux bottles
 *** Calculated with an ambient temperature of 25°C
 **** Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration
 ***** R600a gas. With a R134a gas (for US, CA, Korea, Taiwan): 38 db(A)