



A I temperature cabinet adjustable from 9 to 15° to mature your wines in the best possible conditions.





EAN Code: 3543290002769

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	5	74
Mixed Configuration	I	Į.	98
Minimum Configuration (100% storage)	I	I	98
Standard Configuration	ı	1	98

UNIVERSAL SHELF

Universal shelf: AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level: 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



72 Bottles







« Sliding» 12 Bottles

« Presentation » 6 + 36 Bottles

Artevino AOHUI shelf has a label holder:



Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

- Standard configuration
- Traditional Bordeaux bottles
- Calculated with an ambient temperature of 25°C
- Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration
- R600a gas. With a R134a gas (for US, CA, Korea, Taïwan): 38 db(A)

Range: **OXYGEN**

Model OXP1T98NVD

Fonction: Ageing

Capacity*: 98 Bottles**

A constant temperature due to the dual Heating/Cooling controls.

Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a glass door with highly



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES

Gross weight, packaged (kg)* 70.7 Net weight (kg)* 57.2

1070 x 700 x 750 Dimensions in packaging H x W x D (mm) Dimensions $H \times W \times D(mm)$ 960 x 680 x 690

Color scheme Black

Energy efficiency rating В Acoustic emissions (dB(A))***** 37 Electrical power (W)*** 60 Electrical intensity (A)*** 0.28 Consumption per 24h (KWh) **** 0.47 Annual energy consumption AEc* (kWh/year) **** 172 Ambient temperature operating limit 0 - 30°C

- ✓ Digital electronic controls
- √ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit > Automatic « Winter function »
- √ Temperature fault alarm icon
- √ Interior lining of dimpled aluminium
- √ Glass door
- √ Hygrometry ensured by the principle of thermodynamic pump
- √ 2 adjustable feet
- √ Lock
- √ Storage grid in the low part
- √ Integrated handle into the door frame

nfo@artevino.fr