



A multi-temperatures cabinet with a temperature staggering from 6°C to 20°C to serve your wines in the best possible conditions.



**EAN Code : 3543290003445**

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	5	74
Mixed Configuration	1	1	98
Minimum Configuration (100% storage)	1	1	98
<b>Standard Configuration</b>	<b>1</b>	<b>1</b>	<b>98</b>

## UNIVERSAL SHELF

**Universal shelf : AOHUI**

**Weight:** 2.6 kg

**Type of structure:** slats

**Number of bottles per level :** 12

**Material:** Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



« Storage »  
72 Bottles



« Sliding »  
12 Bottles



« Presentation »  
6 + 36 Bottles

ArteVino AOHUI shelf has a label holder :



Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

\* Standard configuration

\*\* Traditional Bordeaux bottles

\*\*\* Calculated with an ambient temperature of 25°C

\*\*\*\* Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration

\*\*\*\*\* R600a gas. With a R134a gas (for US, CA, Korea, Taiwan): 38 db(A)

Range :	<b>OXYGEN</b>
Model :	<b>OXPM98NVD</b>
Fonction :	<b>Service</b>
Capacity* :	<b>98 Bottles**</b>



A constant temperature due to the dual Heating/Cooling controls.



Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a glass door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

## GENERAL FEATURES

Gross weight, packaged (kg)*	: <b>70,7</b>
Net weight (kg)*	: <b>57,2</b>
Dimensions in packaging H x W x D (mm)	: <b>1070 x 700 x 750</b>
Dimensions H x W x D (mm)	: <b>960 x 680 x 690</b>
Color scheme	: <b>Black</b>

Energy efficiency rating	: <b>B</b>
Acoustic emissions (dB(A))*****	: <b>37</b>
Electrical power (W)***	: <b>65</b>
Electrical intensity (A)***	: <b>0.30</b>
Consumption per 24h (KWh) ****	: <b>0.47</b>
Annual energy consumption AEC* (kWh/year) ****	: <b>172</b>
Ambient temperature operating limit	: <b>12 - 30°C</b>

- ✓ Digital electronic controls with temperature setting range from 6°C to 10°C (lower cabinet area) and 15°C to 20°C (upper cabinet area)
- ✓ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit > Automatic « Winter function »
- ✓ Temperature fault alarm icon
- ✓ Interior lining of dimpled aluminium
- ✓ Glass door
- ✓ Hygrometry ensured by the principle of thermodynamic pump
- ✓ 2 adjustable feet
- ✓ Lock
- ✓ Storage grid in the low part
- ✓ Integrated handle into the door frame